



CRONOS 5W-30 SL/CF

New Generation High Performance Engine Oil Technology

PRODUCT DESCRIPTION

CRONOS 5W-30 is a synthetic engine oil that has been formulated with an excellent combination of synthetic base oils and special additives. It provides unique performance at all kinds of climate and road conditions, especially in inner city and frequent driving.

ADVANTAGES

- Decreases friction inside the engine with the high lubrication property to increase and protect the power of the engine.
- Provides long maintenance periods with its unique resistance to oxidation.
- Provides protection on engine parts with unique features at hard conditions that reach high temperatures.
- Provides superior performance compared to regular oils due to its high performance oil technology.

APPROVALS AND SPECIFICATIONS

- API SL/CF/CF-4

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 5W-30

Test	Unit	Test Method	Ideal Values
Density, 15°C	g/cm ³	ASTM D 4052	0.8506
Viscosity, 40°C	cSt	ASTM D 445	55,73
Viscosity, 100°C	cSt	ASTM D 445	10,02
Viscosity Index	-	ASTM D 2270	169
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	210
TBN	mg KOH/g	ASTM D 2896	7,7

All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.



ADDITIONAL INFORMATION

Package

- 1 L
- 4 L
- 5 L
- 7 L
- 200 L

Storage

- Packages should be stored in cool and well ventilated and closed areas with their caps tightly closed.
- Packages should not be exposed to direct sunlight and seasonal climatic conditions should be avoided.
- Ambient temperature should be under 60°C.

Shelf Life

The shelf life of the product is 2 years maximum under suitable storage conditions.

Health and Safety

Based on the available information CRONOS 5W-30 SL/CF is not harmful for human health when it is used in accordance with the recommendations specified in the “Safety Information Sheets” and in appropriate places. “Safety Information Sheets” can be provided by the company official upon request.

When disposing used products, laws and regulations in force should be followed and the physical and chemical features of the product should be considered during disposal.

ATAK MADENİ YAĞ PAZ. SAN. VE TİC. AŞ

Headquarters : Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility : A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

www.alpetlubricants.com info@atakoil.com