



## DISCUSS AGRI TRANS

### Transmission Oil for Agriculture Vehicles

#### PRODUCT DESCRIPTION

DISCUSS AGRI TRANS is a transmission oil to be used in tractor and the power-shift transmission systems of the other agricultural vehicles. It has been produced with high quality paraffinic mineral base oils and advanced additive packages that provides high performance.

#### ADVANTAGES

- Protects system components due to high anti-wearing properties and EP additives.
- Reduces the noise to the minimum level in the gear systems.
- Reduces the wear.
- Prevents rust, corrosion and foam due to special additives.
- Compatible with all impermeability components.
- Due to its thermal stability and oxidation resistance, it also provides excellent cleaning in the gear system.

#### APPROVALS AND SPECIFICATIONS

- **Transmisyon**

API GL4

ZF TE ML 06E,06F,06K, 17E,21F

- **UTTO**

Ford M2C 134D,

Case New Holland MAT 3525 and 3526,

John Deere J20C, J20D

Massey Ferguson CMS M1145

Volvo WB 101

## CHARACTERISTIC PROPERTIES

Viscosity Class: SAE 10W-30

Analysis	Unit	Analysis Method	Typical Values
Density, 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0,8839
Viscosity, 40 °C	cSt	ASTM D 445	50,85
Viscosity, 100 °C	cSt	ASTM D 445	9,575
Viscosity Index	-	ASTM D 2270	176
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	216

*All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.*

## ADDITIONAL INFORMATION

### Package

- 20 L
- 200 L

### Storage

- Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use.
- Packages should not be exposed to direct sunlight and avoid rapid climatic changes.
- Ambient temperature should not exceed 60 °C.

### Health and Safety

Based on the available information, DISCUSS AGRI TRANS is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Safety Data Sheet" (SDS). SDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties have to be taken into the consideration, and please follow the regional or national regulations.

### ATAK MADENİ YAĞ PAZ. SAN. VE TİC. A.Ş.

Headquarters : Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility : A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

[www.alpetlubricants.com](http://www.alpetlubricants.com) [info@atakoil.com](mailto:info@atakoil.com)