

# PRODUCT DATA SHEET



## **DISCUSS AGRI TRANS S**

## Transmission Oil for Agricultural Machines

### PRODUCT DESCRIPTION

DISCUSS AGRI TRANS S is a transmission oil that has been formulated with high quality base oil. Prevents wear, foam and cuts out noise due to its EP and AW additives. It is developed for using in transmission and hydraulic system of tractors and final drive units of agricultural machines.

## **ADVANTAGES**

- It protects the power transmission system through EP and AW additives.
- · Minimizes scabbing in the gear system.
- Prevents rust, corrosion and foam formation.
- Compatible with all seals.
- It provides very good cleaning of the gear system thanks to its thermal stability and resistance to oxidation.

## APPROVALS AND SPECIFICATION

API GL-4

• Massey Ferguson CMS M1135

Caterpillar TO-2

## **CHARACTERISTIC PROPERTIES**

Analysis	Unit	Analysis Method	Typical Values
Density, @15°C	g/cm³	ASTM D 4052	0,8891
Viscosity, @40°C	cSt	ASTM D 445	92,31
Viscosity, @100°C	cSt	ASTM D 445	10,54
Viscosity Index	-	ASTM D 2270	95
Pour Point	°C	ASTM D 97	-30
Flash Point	°C	ASTM D 92	220

All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.

Document Number: PDS-AV-000402 First Release Date: 01.04.2011 Revision: 01.06.2023



## PRODUCT DATA SHEET



## ADDITIONAL INFORMATION

### **Packages**

- 15 kg
- 200 L

### Storage

- Packages should be stored in cool, well-ventilated and covered areas; and their taps should be thightly closed and sealed when not in use.
- Packages should not be exposed to direct sunlight and avoid rapid climatic changes.
- Ambient temperature should not exceed 60 °C.

### **Health and Safety**

Based on the available information, DISCUSS AGRI TRANS S is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Safety Data Sheet" (SDS). SDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations.

ATAK MADENİ YAĞ PAZ. SAN. VE TİC. A.Ş.

Headquarters: Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility: A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

www.alpetlubricants.com info@atakoil.com

Document Number: PDS-AV-000402 First Release Date: 01.04.2011 Revision: 01.06.2023