

PRODUCT DATA SHEET



PROGRESS LM P SPINDLE GREASE

Cotton Picking Machine Grease

PRODUCT DESCRIPTION

PROGRESS LM P SPINDLE GREASE is a lithium-soap grease with an EP additives developed for use in cotton picking machines. Provides excellent performance at the equipment it used with the help of its quality base oil high performance additive package formulation.

ADVANTAGES

- High oxidation resistance provides long service life.
- High water resistance.
- Decreases system maintenance costs with rust and corrosion protection features.
- Suitable for central pumping systems.

APPLICATIONS

· Cotton picking machines

CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Typical Values
NLGI	-	ASTM D 217	00
Soap Type	-	-	Lithium
Worked Penetration, 25°C	mm/10	ASTM D 217	400 - 430
Color	-	Visual	Green
Base Oil Viscosity, 40°C	cSt	ASTM D 445	20
Four Ball Weld Load	kgf	ASTM D 2596	250
Four Ball Wear	mm	ASTM D 2266	0,4
Oil Separation	% m/m	ASTM D 1742	3
Recommended Working Temperature	°C	-	-10 / 120

All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.

Document No: PDS-G-000705 First Release Date: 01.04.2011 Revision: 01.06.2023



PRODUCT DATA SHEET



ADDITIONAL INFORMATION

Package

- 15 kg
- 180 kg

Storage

- Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use.
- Packages should not be exposed to direct sunlight and avoid rapid climatic changes.
- Ambient temperature should not exceed 60 °C.

Health and Safety

Based on the available information, PROTECTOR LM P SPINDLE GREASE is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Safety Data Sheet" (SDS). SDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties have to be taken into the consideration, and please follow the regional or national regulations.

ATAK MADENİ YAĞ PAZ. SAN. VE TİC. A.Ş.

Headquarters: Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility: A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

www.alpetlubricants.com info@atakoil.com

Document No: PDS-G-000705 First Release Date: 01.04.2011 Revision: 01.06.2023

All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results. They do not constitute a specification and will be revised according to the revisions of the product itself. Also ATAK LUBES declines any liability for user originated damages to this document and contents.