



PROGRESS MP SERIES

Multi-Purpose Greases

PRODUCT DESCRIPTION

PROGRESS MP Series, are multi-purpose calcium soap greases, that have excellent performance in automotive applications. Provide rapid and effective lubrication on low and medium working temperatures at a variety of application area.

ADVANTAGES

- Provide effective protection at systems that exposed to water.
- Economical due to multi-purpose usage.
- High resistance against heat and wear.
- Provide long service life by increasing usage period with its qualified formulation.

CHARACTERISTIC PROPERTIES

Analysis	Unit	Analysis Method	Typical Values			
			MP 0	MP 1	MP 2	MP 3
NLGI	-	ASTM D 217	0	1	2	3
Soap Type	-	-	Calcium			
Base Oil Type	-	-	Mineral			
Worked Penetration, 25 °C	mm/10	ASTM D 217	355-385	310-340	265-295	220-250
Color	-	Visual	Light yellow			
Density, 15 °C	g/cm ³	ASTM D 4052	0,98	0,98	0,98	0,98
Oil Separation	% m/m	ASTM D 1742	2,1	2,2	2,6	2,1
Water Washout	% m/m	ASTM D 1264	4,2	4,1	4,1	4,3
Dropping Point	°C	ASTM D 2265	>95	>95	>95	>95
Recommended Working Temperatures	°C	-	-9/70	-9/70	-9/70	-9/70

All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.

ADDITIONAL INFORMATION

Package

- 4 kg
- 14 kg
- 180 kg

Storage

- Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use.
- Packages should not be exposed to direct sunlight and avoid rapid climatic changes.
- Ambient temperature should not exceed 60 °C.

Health and Safety

Based on the available information, PROGRESS MP SERIES are not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Safety Data Sheet" (SDS). SDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties have to be taken into the consideration, and please follow the regional or national regulations.

ATAK MADENİ YAĞ PAZ. SAN. VE TİC. A.Ş.

Headquarters : Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility : A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

www.alpetlubricants.com info@atakoil.com