



## RIDER 4T 10W-40 4-Stroke Motorcycle Oil

### PRODUCT DESCRIPTION

RIDER 4T 10W-40 is a synthetic engine oil produced with advanced technology that provides superior lubrication and protection for 4-stroke motorcycle engines in the most demanding driving conditions. It can be used safely in all air and water cooled motorcycles that run on single-twin, multi-cylinder, leaded and unleaded gasoline, including sports and scooter models.

### ADVANTAGES

- It provides unmatched engine protection and economy in all climate and usage conditions.
- Thanks to its fully synthetic structure, it provides excellent engine protection against risks that may occur at high speeds.
- Its structure, which keeps oil pressure and consumption under control, provides maximum performance by preventing the formation of deposits.
- It extends the life of the engine by perfectly tolerating the forceful and abrasive effects on the engine due to stop-starts, especially in city use.

### APPROVALS AND SPECIFICATIONS

- API SL
- JASO MB

### CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 10W-40

Test	Unit	Test Method	Typical Values
Density, 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0,8708
Viscosity, 40 °C	cSt	ASTM D 445	98,02
Viscosity, 100 °C	cSt	ASTM D 445	13,62
Viscosity Index		ASTM D 2270	140
TBN	mg KOH/g	ASTM D 2896	9,6

*All the information and figures mentioned above are typical of those obtained with normal production tolerance and verified with quality control test results.*



## ADDITIONAL INFORMATION

### Package

- 1 L

### Storage

- Packages should be stored in cool, well-ventilated and covered areas; and their taps should be tightly closed and sealed when not in use.
- Packages should not be exposed to direct sunlight and avoid rapid climatic changes.
- Ambient temperature should not exceed 60 °C.

### Health and Safety

Based on the available information, RIDER 4T 10W-40 is not expected to produce adverse effects on health when used for the intended application and aligned with the recommendations provided in the; "Safety Data Sheet" (SDS). SDS's are available upon request through your sales contact office or representative.

When disposing the used product, physical and chemical properties has to be taken into the consideration, and please follow the regional or national regulations.

## ATAK MADENİ YAĞ PAZ. SAN. VE TİC. A.Ş.

Headquarters : Yeşilköy Mah. Atatürk Cad. EGS Business Park B2 Blok Kat: 10 34149 Bakırköy-İstanbul/TURKEY

T: +90 212 463 6060 F: +90 212 465 3855

Production Facility : A.O.S.B. 10032 Sok. No: 13 35620 Çiğli-İzmir/TURKEY T: +90 232 328 3128 F: +90 232 328 3025

[www.alpetlubricants.com](http://www.alpetlubricants.com) [info@atakoil.com](mailto:info@atakoil.com)