





TURBOT 20W-50 Quality Diesel Engine Oil

PRODUCT DESCRIPTION

TURBOT NOUVUS 20W-50 is a heavy-duty, high-quality diesel engine oil formulated with high-quality base oils and a balanced additive system that prevents oxidation, wear, corrosion and rust. It can be used in a wide range of heavy-duty diesel engines found in the transportation, construction and agricultural industries.

ADVANTAGES

- Keeps the engine clean thanks to the detergent and dispersant additives it contains.
- Prevents your engine from wearing out thanks to its high viscosity even at high ambient temperatures.
- Protects the engine against rust and wear.

SPECIFICATIONS

• API CC/SC

CHARACTERISTIC PROPERTIES

Viscosity Grades: SAE 20W-50

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm³	ASTM D 4052	0,884
Viscosity, 40 °C	cSt	ASTM D 445	159,7
Viscosity, 100 °C	cSt	ASTM D 445	19,01
Viscosity Index	-	ASTM D 2270	135
Pour Point	°C	ASTM D 97	-24
Flash Point	°C	ASTM D 92	230
Total Base Number	mg KOH/g	ASTM D 2896	8,8







ADDITIONAL INFORMATION

Package

- 1 L
- 4 L
- 7 L
- 9 L
- 16 L
- 20 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at https://www.alpetmadeniyaglari.com/home-english/#

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENI YAĞ PAZARLAMA SANAYI VE TİCARET A. Ş.

Headquarter: Levent Mahallesi, Levent Cad. No:19, Beşiktaş, İstanbul, Turkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Turkiye Tel: +90 232 328 3128 Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com

Page 2 / 2

Document Number: PDS-DE-000217 First Release Date: 01.04.2011 Last Revision Date: 22.10.2024