

CRONOS 10W-30

Long Lasting High Protection

PRODUCT DESCRIPTION

CRONOS 10W-30 is a quality engine oil developed with high quality mineral base oils and high performance additives for use in engines operating with gasoline or LPG. It provides effective protection against wear in valves and bearings, especially in LPG engines, where lubrication is less than gasoline.

ADVANTAGES

- It has a long oil change interval.
- It provides fuel economy compared to oils with higher viscosity such as SAE 10W-40, SAE 15W-40 or SAE 20W-50.
- Thanks to its low viscosity, it ensures easy operation and rapid lubrication of your engine at the first start.
- It prevents the formation of deposits and sludge, keeping your engine as clean as the first day.

SPECIFICATIONS

- API SN/SM/SL/SJ

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 10W-30

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8738
Viscosity, 40°C	cSt	ASTM D 445	74,75
Viscosity, 100°C	cSt	ASTM D 445	11,01
Viscosity Index	-	ASTM D 2270	137
Pour Point	°C	ASTM D 97	-39
Flash Point	°C	ASTM D 92	226
TBN	mg KOH/g	ASTM D 2896	7,5

ADDITIONAL INFORMATION

Packages

- 1 L
- 4 L
- 5 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com