





## **CRONOS 10W-40**

# **Long Lasting High Protection**

### PRODUCT DESCRIPTION

CRONOS 10W-40 is a quality engine oil developed with high quality mineral base oils and high performance additives for use in engines operating with gasoline or LPG. It provides effective protection against wear in valves and bearings, especially in LPG engines, where lubrication is less than gasoline.

## **ADVANTAGES**

- It has a long drain interval.
- Thanks to its high viscosity, it effectively protects engines operating in weather conditions above 40°
  C against wear.
- It prevents the formation of deposits and sludge, ensuring that your engine remains as clean as the first day.

### **SPECIFICATIONS**

• API SN/SM/SL/SJ







## CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 10W-40

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm³	ASTM D 4052	0,8574
Viscosity, 40°C	cSt	ASTM D 445	83,03
Viscosity, 100°C	cSt	ASTM D 445	13,13
Viscosity Index	-	ASTM D 2270	159
Pour Point	°C	ASTM D 97	-39
Flash Point	°C	ASTM D 92	218
TBN	mg KOH/g	ASTM D 2896	7,5

## ADDITIONAL INFORMATION

## Packages

- 1 L
- 4 L
- 5 L
- 200 L

### Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

### Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at <a href="https://www.alpetmadeniyaglari.com/home-english/#">https://www.alpetmadeniyaglari.com/home-english/#</a>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

## ATAK MADENI YAĞ PAZARLAMA SANAYI VE TİCARET A. Ş.

Headquarter: Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Turkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Turkiye Tel: +90 232 328 3128 Fax: +90 232 328 3025 www.alpetmadeniyaglari.com info@alpetlubricants.com

Page 2 / 2

Document Number: PDS-PC-000117 First Release Date: 01.04.2011 Last Revision Date: 21.11.2024