

CRONOS F 0W-30

High Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

CRONOS F 0W-30 is a low sulfated ash (Low SAPS) fully synthetic engine oil developed to meet the Ford specification "WSS-M2C950-A" to help provide long engine life, improved protection and fuel economy in Ecoblue diesel engines found in Ford branded passenger or light commercial vehicles. It can also be used in engines of other vehicle manufacturers, especially Mercedes Benz and Opel, where technical specification requirements and viscosity class are appropriate.

ADVANTAGES

- It has a long oil change interval.
- It provides fuel economy.
- It prevents the shortening of the life of the Diesel Particle Filter (DPF).
- Thanks to its low viscosity, it ensures that your engine starts easily and lubricates quickly at the first start.
- It maintains its performance for a long time thanks to its superior thermal and oxidation stability.

SPECIFICATIONS

- ACEA A5/B5
- ACEA C2
- API SP RC/SP/SN/SM/SL/SJ
- FORD WSS-M2C950-A
- ILSAC GF-6
- MB 227.61/229.61
- OPEL OV 040 1547-G30

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 0W-30

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8490
Viscosity, 40°C	cSt	ASTM D 445	52,18
Viscosity, 100°C	cSt	ASTM D 445	9,85
Viscosity Index	-	ASTM D 2270	178
Pour Point	°C	ASTM D 97	-36
Flash Point	°C	ASTM D 92	210
TBN	mg KOH/g	ASTM D 2896	9,7

ADDITIONAL INFORMATION

Packages

- 11 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com