

## CRONOS F 5W-30

### High Performance Synthetic Engine Oil

#### PRODUCT DESCRIPTION

CRONOS F 5W-30 is a synthetic engine oil developed to meet Ford WSS-M2C913-D requirements, especially for use in gasoline or diesel engines of Ford branded passenger or light commercial vehicles. It can also be used in vehicles of other manufacturers, especially Jaguar and Land Rover vehicles, where the viscosity and performance demands are appropriate. It also covers the old WSS-M2C913-C and WSS-M2C913-B specifications.

#### ADVANTAGES

- It has a long oil change interval.
- It provides fuel economy.
- Thanks to its low viscosity, it ensures easy operation and rapid lubrication of your engine at the first start.
- It maintains its performance for a long time thanks to its superior thermal and oxidation stability.
- It prevents the formation of deposits and sludge in your engine and keeps it clean.

#### SPECIFICATIONS

- ACEA A3/B4, A5/B5
- API SN/SM/SL/SJ
- API CF
- FORD WSS-M2C913-D, C, B
- Mercedes Benz MB 229.1/229.3/229.5
- Renault RN 0700/0710
- Volkswagen VW 501 01/502 00/505 00

# Technical Data Sheet

## CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 5W-30

Test	Unit	Test Method	Typical Values
Density, 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0,8549
Viscosity, 40 °C	cSt	ASTM D 445	65,32
Viscosity, 100 °C	cSt	ASTM D 445	11,08
Viscosity Index	-	ASTM D 2270	163
Pour Point	°C	ASTM D 97	-36
Flash Point	°C	ASTM D 92	210
TBN	mg KOH/g	ASTM D 2896	9,6

## ADDITIONAL INFORMATION

### Packages

- 4 L
- 5 L
- 7 L
- 10,5 L

### Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60 °C.

### Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

## ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

[www.alpetmadeniyaglari.com](http://www.alpetmadeniyaglari.com)

[info@alpetlubricants.com](mailto:info@alpetlubricants.com)