

CRONOS HYDBRID 0W-20

Highest Performance & Fuel Economy Providing Synthetic Engine Oil

PRODUCT DESCRIPTION

CRONOS HYBRID 0W-20 is a low viscosity, fully synthetic gasoline or diesel engine oil developed with the latest technology additives and high performance synthetic base oils, precisely balanced to help provide exceptional engine protection and maximum fuel economy. It can also be used in gasoline engines of hybrid vehicles. It is not suitable for use in older vehicle engines designed to operate with higher viscosity engine oils.

ADVANTAGES

- It has the longest oil change interval.
- It provides the highest fuel economy.
- It extends the life of your engine with its fast start and fast protection in cold weather.
- It provides the longest period of protection for the highest thermal and oxidation stability performance.
- It prevents knocking (LSPI) in your engine.

SPECIFICATIONS

- API SP/SN/SN PLUS/SM/SL/SJ
- Chrysler MS-6395
- FIAT 9.55535-CR-1
- FORD WSS-M2C946-A/947-A
- GM dexos 1 gen 2
- ILSAC GF-6A / GF-6B

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 0W-20

Test	Unit	Test Method	Typical Values
Density, 15 °C	g/cm ³	ASTM D 4052	0,8543
Viscosity, 40 °C	cSt	ASTM D 445	39,46
Viscosity, 100 °C	cSt	ASTM D 445	7,54
Viscosity Index	-	ASTM D 2270	162
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	230
TBN	mg KOH/g	ASTM D 2896	7,2

ADDITIONAL INFORMATION

Packages

- 1 L
- 4 L
- 5 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60 °C.

Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com