

CRONOS LA 0W-30

High Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

CRONOS LA 0W-30 is a very high-performance, high-quality, synthetic engine oil containing low sulphated ash and phosphorus (Low SAPS), designed to provide long life and maintain efficiency in systems such as Diesel Particulate Filter, (DPF), Selective Catalytic Reductant (SCR), etc., which are used to reduce exhaust gas emissions in passenger cars, light commercial vehicles or vans with both diesel and gasoline engines, especially in Peugeot-Citroen and Fiat group vehicles under the Stellantis umbrella..

ADVANTAGES

- It has the longest drain interval.
- It provides fuel economy compared to SAE 5W-30 or higher viscosity class oils.
- Helps maintain the efficiency of exhaust emission reduction systems in both diesel and gasoline vehicles.
- Allows operation at high temperatures without oil thickening and oil deterioration due to oxidation.
- Thanks to its high fluidity at low temperatures, it quickly fulfills its lubrication duty at the first start of the engine in cold weather.
- Helps your engine stay clean as the first day.

SPECIFICATIONS

- ACEA C2
- API SP/SN/SM/SL/SJ
- FIAT 9.55525-GS1/DS1
- PSA B71 2302/2312

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 0W-30

Test	Unit	Test Method	Typical Values
Density, 15 °C	g/cm ³	ASTM D 4052	0,8428
Viscosity, 40 °C	cSt	ASTM D 445	53,46
Viscosity, 100 °C	cSt	ASTM D 445	9,84
Viscosity Index	-	ASTM D 2270	173
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	218
TBN	mg KOH/g	ASTM D 2896	7,2

ADDITIONAL INFORMATION

Packages

- 1 L
- 4 L
- 5 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60 °C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com