

Technical Data Sheet



CRONOS PREMIUM 10W-40

High Performance Engine Oil

PRODUCT DESCRIPTION

CRONOS PREMIUM 10W-40 is a high performance mineral engine oil developed to provide high level of protection and performance and to be used in gasoline or diesel engines.

ADVANTAGES

- It has a long oil change interval.
- It allows operation at high temperatures without oil thickening and oil deterioration due to oxidation.
- It effectively protects your engine against wear even at high temperatures.
- It helps your engine stay clean as the first day.

SPECIFICATIONS

- API A3/B3, A3/B4
- API SN/SM/SL/SJ/CF
- Mercedes Benz Approval 229.3/226.5
- PSA B71 2300
- Renault RN 0700/0710
- Volkswagen 501 01/505 00

Document Number: TDS-A52-00B165

Page 1 / 2

First Release Date: 01.04.2011

Last Revision Date: 21.11.2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. ALPET LUBRICANTS cannot be held responsible for any damage or loss that may arise from abnormal or unintended use of the product or from the inherent dangers and consequences of this product.



Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 10W-40

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8675
Viscosity, 40°C	cSt	ASTM D 445	98,59
Viscosity, 100°C	cSt	ASTM D 445	14,70
Viscosity Index	-	ASTM D 2270	155
Pour Point	°C	ASTM D 97	-33
Flash Point	°C	ASTM D 92	228
TBN	mg KOH/g	ASTM D 2896	10,0

ADDITIONAL INFORMATION

Packages

- 1 L
- 3 L
- 4 L
- 5 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at https://www.alpetmadeniyaglari.com/home-english/#

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Turkiye : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Turkiye Tel: +90 232 328 3128 Fax: +90 232 328 3025 Plant www.alpetmadeniyaglari.com info@alpetlubricants.com

Document Number: TDS-A52-00B165

Page 2 / 2 First Release Date: 01.04.2011

Last Revision Date: 21.11.2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. ALPET LUBRICANTS cannot be held responsible for any damage or loss that may arise from abnormal or unintended use of the product or from the inherent dangers and consequences of this product.