

CRONOS RN LA 720 5W-30

High Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

CRONOS RN LA 720 5W-30 is a high performance synthetic engine oil containing low sulphated ash and phosphorus (Low SAPS), designed to maintain efficiency and ensure long life in systems such as Diesel Particulate Filter, (DPF) Selective Catalytic Reduction, (SCR) etc. that reduce exhaust gas emissions in passenger cars, light commercial vehicles and vans with gasoline or diesel engines, especially Renault.

ADVANTAGES

- It has the long drain interval.
- Helps maintain the efficiency of exhaust emission reduction systems in both diesel and gasoline vehicles.
- Allows operation at high temperatures without oil thickening and oil deterioration due to oxidation.
- Effectively protects your engine against wear even at high temperatures.
- Helps your engine stay as clean as the first day.

SPECIFICATIONS

- ACEA C4
- Mercedes Benz Approval 226.51
- Renault RN 720

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 5W-30

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8527
Viscosity, 40°C	cSt	ASTM D 445	65,28
Viscosity, 100°C	cSt	ASTM D 445	11,13
Viscosity Index	-	ASTM D 2270	166
Pour Point	°C	ASTM D 97	-36
Flash Point	°C	ASTM D 92	228
TBN	mg KOH/g	ASTM D 2896	6,9

ADDITIONAL INFORMATION

Packages

- 1 L
- 5 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com