

CRONOS SUPREME C 5W-30

Superior Performance Synthetic Engine Oil

PRODUCT DESCRIPTION

CRONOS SUPREME C 5W-30 is a synthetic, mid SAPS, gasoline or diesel engine oil developed with advanced technology ingredients to help provide exceptional cleaning power and wear protection and to be fully compatible with Diesel Particulate Filters (DPFs) and Gasoline Catalytic Converters (CATs) and meets the requirements of many leading automobile manufacturers.

ADVANTAGES

- It has a long oil change interval.
- It provides fuel economy.
- Thanks to its low viscosity, it ensures that your engine starts easily and lubricates quickly at the first start.
- It prevents knocking (LSPI) especially in gasoline direct injection turbocharged engines.
- It prevents the formation of deposits and sludge in your engine and keeps it clean.
- It ensures that the Diesel Particle Filter (DPF), Gasoline Catalytic Converter (CAT), etc. equipment in the exhaust system work efficiently.

SPECIFICATIONS

- ACEA C3
- API SP/SN/SM/SL/SJ
- BMW LL-04
- Mercedes Benz MB 229.31/229.51/229.52
- Opel OV 040 1547-D30/G30
- Porsche C30
- Volkswagen VW 504 00/507 00

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Viscosity Grade: SAE 5W-30

Test	Unit	Test Method	Typical Values
Density, 15°C	g/cm ³	ASTM D 4052	0,8524
Viscosity, 40°C	cSt	ASTM D 445	63,08
Viscosity, 100°C	cSt	ASTM D 445	10,68
Viscosity Index	-	ASTM D 2270	160
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	220
TBN	mg KOH/g	ASTM D 2896	7,5

ADDITIONAL INFORMATION

Packages

- 1 L
- 4 L
- 5 L
- 7 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com