

**ATF CVT****Continuous Variable Synthetic Transmission Fluid****PRODUCT DESCRIPTION**

ATF CVT is a premium quality synthetic transmission oil designed to meet the service filling needs of a wide range of wet type continuously variable ratio (CVT) transmissions of European and Asian automobile manufacturers, produced with selected high quality synthetic base oils combined with an advanced additive system, and can be used in both belt and chain transmissions.

**ADVANTAGES**

- Helps to provide excellent protection against wear, rust and corrosion and to preserve the life of the transmission.
- Stable, optimised friction properties and exceptional torque capacity retention provide a smooth shifting feel without NVH (Noise, Vibration and Harshness) concerns.
- Excellent flow properties provide instant lubrication and protection during cold start-up.
- Excellent oil oxidation and shear stability contribute to long oil life.
- Effective foam control properties and compatibility with sealing materials prevent oil consumption due to oil leakage.
- Should not be used in dual clutch automated transmissions (DCT)

**SPECIFICATIONS**

- BMW Mini Cooper EZL 799
- Daihatsu Ammix CVT, CVT Fluid DC, CVT Fluid DFE
- Dodge/Jeep/Chrysler NS-2/CVTF +4
- GM DEX-CVT
- Honda Z-1, HMMF, HCF2 (CVT model without clutch)
- Hyundai/Kia SP-III (CVT model), CVT J1, CVTF-J4
- Mazda JWS 3320
- Mitsubishi (Diaqueen) SP-III (CVT Modeli), CVTF-J1
- Nissan NS-1, NS-2, NS-3

# Technical Data Sheet

- Subaru ECVT, iCVT
- Suzuki CVTF TC/3320, NS-2, CVT Green 1 & 2
- Toyota CVTF TC, CVTF FE

## CHARACTERISTIC PROPERTIES

Method	Unit	Test Method	Typical Characteristics
Density, 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0,913
Viscosity, 40 °C	cSt	ASTM D 445	34,27
Viscosity, 100 °C	cSt	ASTM D 445	7,22
Viscosity Index		ASTM D 2270	182
Pour Point	°C	ASTM D 97	-51
Flash Point	°C	ASTM D 92	160

## ADDITIONAL INFORMATION

### Packages

- 1 L

### Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60 °C.

### Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

## ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

[www.alpetmadeniyaglari.com](http://www.alpetmadeniyaglari.com)

[info@alpetlubricants.com](mailto:info@alpetlubricants.com)