

ATF DEXRON II

Automatic Transmission Fluid

PRODUCT DESCRIPTION

ATF DEXRON II is a mineral-based automatic transmission oil produced with conventional base oils together with a quality additive system, designed for automatic transmissions in older vehicles manufactured before 1994 that require Dexron IID performance. It can also be used as power assisted steering oil.

ADVANTAGES

- It resists varnish, sludge and deposit formation to ensure effective operation throughout its life thanks to its high thermal and oxidation stability.
- It is compatible with all common sealing materials used in transmissions.
- It provides smooth and comfortable gear shifts and less fluid loss in difficult working conditions thanks to its effective foam control features.
- It contributes to long oil life thanks to its oxidation and shear stability.

SPECIFICATIONS

- Chrysler ATF+, +2
- Ford WSS-M2C138-CJ, WSS-M2C166-H
- GM TASA, DEXRON®-II, DEXRON®-IID
- Hyundai/Kia Dex-II/ SP-II
- Mazda ATF D-II
- Renault Matic D2
- Toyota ATF D-II
- 3 or 4 speed ZF automatic transmissions

Technical Data Sheet

CHARACTERISTIC PROPERTIES

Method	Unit	Test Method	Typical Characteristics
Density, 15 °C	g/cm ³	ASTM D 4052	0,8688
Viscosity, 40 °C	cSt	ASTM D 445	35,48
Viscosity, 100 °C	cSt	ASTM D 445	7,317
Viscosity Index		ASTM D 2270	178
Pour Point	°C	ASTM D 97	-42
Flash Point	°C	ASTM D 92	210

ADDITIONAL INFORMATION

Packages

- 1 L
- 3 L
- 20 L
- 200 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60 °C.

Health and Safety

Health and Safety recommendations for this product can be found on the “Safety Data Sheet” (SDS) at <https://www.alpetmadeniyaglari.com/home-english/#>

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Türkiye

Plant : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Türkiye

Tel: +90 232 328 3128

Fax: +90 232 328 3025

www.alpetmadeniyaglari.com

info@alpetlubricants.com