

Technical Data Sheet



ATF HFS

Power Assisted Steering Oil

PRODUCT DESCRIPTION

ATF HFS is a mineral based power steering fluid produced with conventional base oils together with a quality additive system for use in automatic transmissions or power assisted hydraulic steering systems in older vehicles manufactured before 1967. Do not use in systems requiring GM Dexron II or higher performance.

ADVANTAGES

- Thanks to its high thermal and oxidation stability, it resists varnish, sludge and sediment formation to ensure effective operation throughout its life.
- It protects the parts in the hydraulic steering system against rust and wear.
- It contributes to long oil life thanks to its oxidation and shear stability.

SPECIFICATIONS

• GM Type A Suffix A (TASA)

Document Number: PDS-TF-000604

Page 1 / 2 First Release Date: 01.04.2011

Last Revision Date: 24.12.2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. ALPET LUBRICANTS cannot be held responsible for any damage or loss that may arise from abnormal or unintended use of the product or from the inherent dangers and consequences of this product.



Technical Data Sheet

CHARACTERISTIC PROPERTIES

Method	Unit	Test Method	Typical Characteristics
Density, 15°C	g/cm ³	ASTM D 4052	0,8746
Viskosity, 40°C	cSt	ASTM D 445	41,89
Viskosity, 100°C	cSt	ASTM D 445	7,266
Viskosity Index		ASTM D 2270	138
Pour Point	°C	ASTM D 97	-30
Flash Point	°C	ASTM D 92	230

ADDITIONAL INFORMATION

- Packages
 - 1 L

Storage

- Packages should be stored in well-ventilated and closed areas with their lids tightly closed.
- Packages should not be exposed to direct sunlight and should always be stored under 60°C.

Health and Safety

Health and Safety recommendations for this product can be found on the "Safety Data Sheet" (SDS) at https://www.alpetmadeniyaglari.com/home-english/#

Used oils should not be poured into underground or any water reservoir, sewer connection, or garbage. Gloves should be used to avoid skin diseases in prolonged contact with used oils. If used oil comes into contact with the skin, it should be washed immediately with plenty of soap and water. If irritation and redness occur in skin contact, a doctor should be consulted immediately.

ATAK MADENİ YAĞ PAZARLAMA SANAYİ VE TİCARET A. Ş.

Headquarter : Zorlu Holding Gültepe Girişi, Büyükdere Cad. No:199, Kat: -1, 22. Mahal, 34394, Levent, İstanbul, Turkiye : A.O.S.B., 10032 Sok., No: 13, 35620, Çiğli, İzmir, Turkiye Tel: +90 232 328 3128 Fax: +90 232 328 3025 Plant www.alpetmadeniyaglari.com

info@alpetlubricants.com

Document Number: PDS-PC-000604

Page 2 / 2 First Release Date: 01.04.2011

Last Revision Date: 24.12.2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. ALPET LUBRICANTS cannot be held responsible for any damage or loss that may arise from abnormal or unintended use of the product or from the inherent dangers and consequences of this product.